

**This Page Is Inserted by IFW Operations
and is not a part of the Official Record**

BEST AVAILABLE IMAGES

**Defective images within this document are accurate representations of
the original documents submitted by the applicant.**

Defects in the images may include (but are not limited to):

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORLED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Patent Abstracts of Japan

PUBLICATION NUMBER : 60155959
PUBLICATION DATE : 16-08-85


APPLICATION DATE : 25-01-84
APPLICATION NUMBER : 59012405

APPLICANT : MATSUSHITA ELECTRIC WORKS LTD;

INVENTOR : KOBAYASHI YOSHIKI;

INT.CL. : G01N 27/38 // C12Q 1/00

TITLE : MEASUREMENT USING BIOSENSOR



ABSTRACT : PURPOSE: To extend the life of a biosensor by applying an opposite potential to an electrode of the biosensor having a physiologically active substance immobilized during the measuring operation of an object to be inspected in a measurement to remove a matter eventually adsorbed on the electrode.

CONSTITUTION: A solvent 4 in a solvent reservoir 1 runs through a tube 3 with a pump 5, a certain voltage is applied to a working electrode 8 and an opposed electrode 9 from a power source 10 and then, a sample is injected into an inlet 6. Current value obtained by measuring the magnitude of the current flowing between the working electrode 8 and the opposed electrode 9 corresponds to the mass of an object to be inspected. When a potential is applied to the working electrode, substance other than substances to be inspected in the sample is adsorbed on a film having a physiologically active substance immobilized to reduce the sensitivity gradually. To counter this, an opposite potential to that during the measuring operation is applied to the working electrode 8 and the opposed electrode 9 running a liquid such as solvent through the tube 3 between the measuring operations to remove matter adsorbed during the measuring operation thereby extending the life of a biosensor.

COPYRIGHT: (C)1985,JPO&Japio